

COMMONWEALTH OF VIRGINIA

Department of Mines, Minerals and Energy
Division of Mined Land Reclamation

Laurel Branch of Lick Creek TSS Wasteload Report 2017-Q3

10-01-2016 to 09-30-2017

Watershed Information

Stressor:TSSWatershed Acres:2,674Wasteload Allocation:2,600Watershed Permits:0EPA TMDL Approval Date:4/10/2008Watershed Outfalls:0

Watershed Wasteload and Reduction Summary¹

	Pre-TMDL Wasteloads ²	Post-TMDL Wasteloads ³	Total				
Wasteload Allocation Available ⁴	2,600	2,600	2,600				
Wasteload ⁵	0	0	0				
Wasteload Balance	2,600	2,600	2,600				
Wasteload Reduction Required ⁶	0	0	0				
Percent Reduction Required ⁷	0.0 %	0.0 %	NaN				

¹ Wasteload units are in kg/year unless otherwise noted.

² Pre-TMDL Wasteloads are calculated from outfalls existing before the EPA's approval of the TMDL.

³ Post-TMDL wasteloads are calculated from outfalls added after the EPA's approval of the TMDL.

⁴ The wasteload allocation available for pre-TMDL outfalls is the approved wasteload allocation for the watershed.

The wasteload allocation available for post-TMDL outfalls is any remaining balance not used by pre-TMDL outfalls.
⁵ Wasteloads are calculated on a quarterly basis using reported monitoring data, which includes samples taken

when an alternate effluent limitation (AEL) precipitation event is utilized.

⁶ In order to meet the wasteload allocation, all negative wasteload balance (i.e. the amount of wasteload

exceeding the wasteload allocation) must be reduced.

The percent reduction required is used to assign wasteload reductions to permits when the watershed's wasteload exceeds the available wasteload allocation.

Permit Wasteload and Reduction Summary⁸

Permit Number	Pre-TMDL Wasteload ⁹	Pre-TMDL Reduction Required ¹⁰	Post-TMDL Wasteload ¹¹	Post-TMDL Reduction Required ¹²	Total Wasteload	Total Wasteload Reduction Required
Total	0	0	0	0	0	0

Wasteload units are in kg/year unless otherwise noted.
 The wasteload calculated from outfalls existing before the EPA's approval of the TMDL.

¹⁰ Pre-TMDL reduction calculated by multiplying the pre-TMDL wasteload by the watershed's pre-TMDL percent reduction required.

The wasteload
 Post-TMDL reduction calculated by multiplying the post-TMDL wasteload by the watershed's post-TMDL percent reduction required.